

برگ الحاقی تقاضای خرید کالای پروژه / خرید مستقیم
PROJECT / DIRECT CHARGE MATERIALS REQUEST
CONTINUATION SHEET



REQUEST NO.

شماره تقاضا

شماره قلم ITEM NO.	شماره طبقه بندی کالا MESC NO.	واحد کالا UNIT	شرح کالا DESCRIPTION	مقدار REQUIRED QTY.	ارزش تقریبی قلم VALUE (EST.)	م.و.س M.O.S	ن.ت. N.T.	S.O.S	اطلاعات منبع کالا CROSS REF.			شماره قلم ITEM
									شماره انبار STORE NO.	اداره ADMIN	شماره درخواست REQUEST NO.	
04		NO	CROSS OVER SUB (X-OVER) SIZE: 5", 18 PPF, N.VAM PIN x 4 1/2 IF (NC 50) BOX, 16.6 PPF TYPE: SMLS, PSL 2 MAX OD: 5", MIN ID: 3.750", DRIFT DIA: 3.625", LENGTH: 2-2.5 FT MATERIAL: 4140 AS PER API 5CT & NACE MR-01-75 ISO 15156 INTERNAL YIELD PRESSURE: 10140 PSI COLLAPSE PRESSURE: 10490 PSI PIP BODY STRENGTH: 422 KLB	10								
05		NO	CROSS OVER SUB (X-OVER) SIZE: 5", 18 PPF, VAM FJL PIN x 4 1/2 IF (NC 50) BOX, 16.6 PPF TYPE: SMLS, PSL 2 MAX OD: 5", MIN ID: 3.750", DRIFT DIA: 3.625", LENGTH: 2-2.5 FT MATERIAL: 4140 AS PER API 5CT & NACE MR-01-75 ISO 15156 INTERNAL YIELD PRESSURE: 10140 PSI COLLAPSE PRESSURE: 10490 PSI PIP BODY STRENGTH: 422 KLB	10								
06		NO	CROSS OVER SUB (X-OVER) SIZE: 4 1/2", 13.5 PPF, N.VAM PIN x 3 1/2 IF (NC 38) BOX 15.5 PPF TYPE: SMLS, PSL 2 MAX OD: 4 1/2", MIN ID: 2.992", DRIFT DIA: 2.867", LENGTH: 2-2.5 FT MATERIAL: 4140 AS PER API 5CT & NACE MR-01-75 ISO 15156 INTERNAL YIELD PRESSURE: 9020 PSI COLLAPSE PRESSURE: 8540 PSI PIP BODY STRENGTH: 307 KLB	70								
07		NO	CROSS OVER SUB (X-OVER) SIZE: 9 5/8", 53.5 PPF, N.VAM PIN x 4 1/2 IF (NC 50) BOX, 16.6 PPF TYPE: SMLS, PSL 2 MAX OD: 9 5/8", MIN ID: 3.750", DRIFT DIA: 3.625", LENGTH: 3-3.5 FT MATERIAL: 4140 AS PER API 5CT & NACE MR-01-75 ISO 15156 INTERNAL YIELD PRESSURE: 5750 PSI COLLAPSE PRESSURE: 3090 PSI PIP BODY STRENGTH: 422 KLB	10								
08		NO	CROSS OVER SUB (X-OVER) SIZE: 13 3/8", 72 PPF, N.VAM PIN x 4 1/2 IF (NC 50) BOX, 16.6 PPF TYPE: SMLS, PSL 2 MAX OD: 13 3/8", MIN ID: 3.750", DRIFT DIA: 3.625", LENGTH: 3-3.5 FT MATERIAL: 4140 AS PER API 5CT & NACE MR-01-75 ISO 15156 INTERNAL YIELD PRESSURE: 5380 PSI COLLAPSE PRESSURE: 2670 PSI PIP BODY STRENGTH: 422 KLB	10								

DELIVERY TIME (ACCORDING TENDER DOCUMENTS):	9 MONTHS
DELIVERY LOCATION:	DALAN DRILLING WAREHOUSE
PACKING:	BUNDLE
INSPECTION:	ALL COST OF INSPECTION ARE RESPONSIBILITY OF MANUFACTURER/SUPPLIER.PROCEDURE OF INSPECTIN IS DETERMINED BY ICOFC TECHNICAL INSPECTION DEPARTMENT.
REFERENCE STANDARDS:	API 5CT - NACE MR 0175 - API 5C3 LAST EDITION- API 5DP - API 7 - API 7G
PROTECTORS (2 ENDS):	METALLOPLASTIC CLOSE END UNLIFTABLE.

[Handwritten signatures and stamps]