





شرکت نفت مناطق مرکزی ایران

PROJECT / DIRECT CHARGE MATERIALS REQUEST CONTINUATION SHEET

شماره تقاضا

REQUEST NO.

ردیف ITEM NO.	شرح کالا DESCRIPTION	مقدار REQUIRED QTY.	مبلغ VALUE (EST.)	تاریخ DATE	ردیف ITEM NO.	شرح کالا DESCRIPTION	مقدار REQUIRED QTY.	مبلغ VALUE (EST.)	تاریخ DATE
04	TIE BACK SLEEVE PBR, 7", 32 PPF, DRIFT DIAMETER 5.969" THREAD: GAS TIGHT PREMIUM CONNECTION BOX DOWN (SHALL BE FULL INTERCHANGEABLE WITH NEW VAM) MATERIAL: T-95 AS PER API 5CT MIN. INTERNAL YIELD PRESSURE: 10760PSI MIN. COLLAPSE PRESSURE: 9740 PSI, MIN. TENSILE STRENGTH: 885KLB LENGTH: 6 FT	10			05	FLOAT SHOE 7", 32 PPF, DRIFT DIAMETER 5.969", T-95 AS PER API 5CT, GAS TIGHT PREMIUM CONNECTION BOX UP, PDC DRILLABLE MIN. INTERNAL YIELD PRESSURE: 10760PSI MIN. COLLAPSE PRESSURE: 9740 PSI, MIN. TENSILE STRENGTH: 885KLB (SHALL BE FULL INTERCHANGEABLE WITH NEW VAM)	10		
06	LATCH DOWN COLLAR WITH PDC DRILLABLE PROFILE C/W BALL, 7", 32 PPF, DRIFT DIAMETER 5.969" T-95 AS PER API 5CT, GAS TIGHT PREMIUM CONNECTION, NON ROTATING FEATURES FOR PLUGS MIN. INTERNAL YIELD PRESSURE: 10760PSI MIN. COLLAPSE PRESSURE: 9740 PSI, MIN. TENSILE STRENGTH: 885KLB (SHALL BE FULL INTERCHANGEABLE WITH NEW VAM)	10			07	TIE BACK SEAL ASSY (SEAL NIPPLE) 7", 32 PPF, DRIFT DIAMETER 5.969", PREMIUM CONNECTION T-95 AS PER API 5CT, BOX UP TEMPERATURE RATING: 250° - 360° F MIN. INTERNAL YIELD PRESSURE: 10760PSI MIN. COLLAPSE PRESSURE: 9740 PSI, MIN. TENSILE STRENGTH: 885KLB NUMBERS OF SEALS: SPECIFIED BY MANUFACTURE SEALS OD: SPECIFIED BY MANUFACTURE LENGTH: 6 FT (AS PER ITEM 4) SEALS MATERIAL: 1LNBR (SHALL BE FULL INTERCHANGEABLE WITH NEW VAM)	05		
08	LATCH DOWN COLLAR WITH PDC DRILLABLE PROFILE C/W BALL, 7", 32 PPF, DRIFT DIAMETER 5.969" T-95 AS PER API 5CT, GAS TIGHT PREMIUM CONNECTION, NON ROTATING FEATURES FOR PLUGS MIN. INTERNAL YIELD PRESSURE: 10760PSI MIN. COLLAPSE PRESSURE: 9740 PSI, MIN. TENSILE STRENGTH: 885KLB (SHALL BE FULL INTERCHANGEABLE WITH NEW VAM)	05							

کمیسیون مناقصات  
۴ / ۳ / ۱۴۰۵  
شرکت نفت مناطق مرکزی ایران




Handwritten signature

Handwritten signature

Handwritten signature





## PROJECT / DIRECT CHARGE MATERIALS REQUEST CONTINUATION SHEET

REQUEST NO.

ITEM NO	MATERIAL NO	DESCRIPTION	REQUIRED QTY.	VALUE (\$)	CROSS REF.	STOCK NO	REQUEST NO
09	NO	10 SET HYD LINER HANGER TANDEM 7", 32#, T-95 W/ 5 SET TIE BACK 7", 32#, T-95  SETTING COLLAR (LC) 7", 32 PPF, DRIFT DIAMETER 5.969", PREMIUM CONNECTION, PIN x PIN T-95 AS PER API SCT. FOR CONNECTION TO RUNNING AND SETTING TOOLS MIN. INTERNAL YIELD PRESSURE: 10760PSI MIN. COLLAPSE PRESSURE: 9740 PSI, MIN. TENSILE STRENGTH: 885KLB (SHALL BE FULL INTERCHANGEABLE WITH NEW VAM)	05				
10	NO	TIE BACK SLEEVE PBR, 7", 32 PPF, DRIFT DIAMETER 5.969" THREAD: GAS TIGHT PREMIUM CONNECTION BOX DOWN (SHALL BE FULL INTERCHANGEABLE WITH NEW VAM) MATERIAL: T-95 AS PER API SCT MIN. INTERNAL YIELD PRESSURE: 10760PSI MIN. COLLAPSE PRESSURE: 9740 PSI, MIN. TENSILE STRENGTH: 885KLB LENGTH: 6 FT	05				
11	NO	PACK OFF BUSHING 7", 32 PPF, DRIFT DIAMETER 5.969", PREMIUM CONNECTION, PIN x BOX T-95 AS PER API SCT, PDC DRILLABLE MIN. INTERNAL YIELD PRESSURE: 10760PSI MIN. COLLAPSE PRESSURE: 9740 PSI, MIN. TENSILE STRENGTH: 885KLB (SHALL BE FULL INTERCHANGEABLE WITH NEW VAM)	05				
12	NO	LINER WIPER PLUG 7" TO WIPE CEMENT INSIDE 32 PPF & 35 PPF LINER, PDC DRILLABLE, NON ROTATING TO LAND AND LOCK INSIDE LDC MATERIAL: SPECIFIED BY MANUFACTURE ELASTOMER MATERIAL: NBR TEMPERATURE RATING: 250° - 300° F	15				
13	NO	PUMP DOWN PLUG MATERIAL: SPECIFIED BY MANUFACTURE, NON ROTATING TO LAND AND LOCK INSIDE WIPER PLUG ELASTOMER MATERIAL: NBR TEMPERATURE RATING: 250° - 300° F FOR 5" DRILL PIPE, PDC DRILLABLE	15				
14	NO	FLOAT COLLAR 7", 32 PPF, DRIFT DIAMETER 5.969", T-95, AS PER API SCT, GAS TIGHT PREMIUM CONNECTION BOX UP, PIN DOWN, PDC DRILLABLE MIN. INTERNAL YIELD PRESSURE: 10760PSI MIN. COLLAPSE PRESSURE: 9740 PSI, MIN. TENSILE STRENGTH: 885KLB (SHALL BE FULL INTERCHANGEABLE WITH NEW VAM)	10				
15	SET	SETTING TOOL FOR HYDRAULIC LINER HANGER 7" WITH ALL ACCESSORIES	02				

کمیسیون مناقصات

۱۴۰۵ / ۳ / ۴	
شرکت نفت مناطق مرکزی ایران	

