

SHP-3190704145

۵۵۲۶
فهرست

MTI		ADMIN		REQUEST NO.		PROJECT / DIRECT CHARGE MATERIALS REQUEST		نیاز کار ۳ ماهه جاری		تقاضای خرید کالای پروژه / خرید مستقیم		ایجاد / اصلاح / ابطال	
26	05	31	31	31	31	31	31	31	31	31	31	31	31
ACCT NO.		STORE NO.		REQ. DATE		REQ. DATE		TOTAL QTY.		TOTAL VALUE (R)		PLAN NO.	
1405/08		1405/08		1405/08		1405/08		68		1405/08		1405/08	
DESCRIPTION		UNIT		REQ. DATE		REQ. DATE		TOTAL QTY.		TOTAL VALUE (R)		PLAN NO.	
5 SET HYD LINER HANGER TANDEM 7", 29#, L-80 W/ 3 SET TIE BACK 7", 29#, L-80		NO		1405/08		1405/08		68		1405/08		1405/08	
SETTING COLLAR SETTING PROFILE (LG) FOR CONNECTION TO RUNNING AND SETTING TOOLS MATERIAL: L-80/TYP-1 AS PER API 5CT MIN. INTERNAL YIELD PRESSURE: 8160 PSI MIN. COLLAPSE PRESSURE: 7030 PSI, MIN. TENSILE STRENGTH: 676 KLB THREAD: GAS TIGHT PREMIUM CONNECTION (SHALL BE FULL INTERCHANGEABLE WITH NEW VAM) TEMPERATURE RATING: 250° - 300° F, WORKING PRESSURE: 5000 - 7000 PSI HOST CASING: 9 5/8", 43.5-58.4 PPF, V-150, D.D. RANGE 8.375" - 8.599"		NO		1405/08		1405/08		68		1405/08		1405/08	
PACK OFF BUSHING 7", 29 PPF, SPECIAL DRIFT DIAMETER 6-1/8", PREMIUM CONNECTION, PIN x BOX L-80/TYP-1 AS PER API 5CT, PDC DRILLABLE MIN. INTERNAL YIELD PRESSURE: 8160 PSI MIN. COLLAPSE PRESSURE: 7030 PSI, MIN. TENSILE STRENGTH: 676 KLB (SHALL BE FULL INTERCHANGEABLE WITH NEW VAM)		NO		1405/08		1405/08		68		1405/08		1405/08	
LINER HANGER & ACC. HYDRAULIC SET, DOUBLE CONE (TANDEM CONE), 7", 29 PPF SPECIAL DRIFT DIAMETER 6-1/8" MATERIAL: L-80/TYP-1 AS PER API 5CT MIN. INTERNAL YIELD PRESSURE: 8160 PSI MIN. COLLAPSE PRESSURE: 7030 PSI, MIN. TENSILE STRENGTH: 676 KLB THREAD: GAS TIGHT PREMIUM CONNECTION (SHALL BE FULL INTERCHANGEABLE WITH NEW VAM) MIN. SETTING PRESSURE: (SHALL BE CONFIRMED WITH MANUFACTURER) MAX. SETTING PRESSURE: (SHALL BE CONFIRMED WITH MANUFACTURER) TEMPERATURE RATING: 250° - 300° F, WORKING PRESSURE: 5000 - 7000 PSI MATERIAL OF SEAL ELEMENT: HNBR HOST CASING: 9 5/8", 43.5 - 58.4 PPF, V-150, D.D. RANGE 8.375" - 8.599" NOTE: SHALL BE SUITABLE TO RUN & SET IN OIL BASE MUD		NO		1405/08		1405/08		68		1405/08		1405/08	



شرکت نفت مناطق مرکزی ایران
۱۴۰۵ / ۱۳ / ۴
کمیسیون مناقصات




توسعه‌یافته‌ی تقاضای خرید کالای پروژه / خرید مستقیم

PROJECT / DIRECT CHARGE MATERIALS REQUEST CONTINUATION SHEET

شماره تقاضا

REQUEST NO.

ITEM NO	WESC NO	شرح کالا	توضیحات	REQUIRE QTY	VALUE (EST)	تاریخ تقاضا	تاریخ بررسی	تاریخ تایید	CROSS REF.	تاریخ تایید	تاریخ تایید	تاریخ تایید
04		TIE BACK SLEEVE PBR, 7", 29 PPF, SPECIAL DRIFT DIAMETER 6-1/8" THREAD: GAS TIGHT PREMIUM CONNECTION BOX DOWN (SHALL BE FULL INTERCHANGEABLE WITH NEW VAM) MATERIAL: L-80/TYP-1 AS PER API 5CT MIN. INTERNAL YIELD PRESSURE: 8160 PSI MIN. COLLAPSE PRESSURE: 7030 PSI, MIN. TENSILE STRENGTH: 676 KLB LENGTH: 6 FT	NO	05								
05		FLOAT SHOE 7", 29 PPF, SPECIAL DRIFT DIAMETER 6-1/8", L-80/TYP-1 AS PER API 5CT, GAS TIGHT PREMIUM CONNECTION BOX UP, PDC DRILLABLE MIN. INTERNAL YIELD PRESSURE: 8160 PSI MIN. COLLAPSE PRESSURE: 7030 PSI, MIN. TENSILE STRENGTH: 676 KLB (SHALL BE FULL INTERCHANGEABLE WITH NEW VAM)	NO	05								
06		LATCH DOWN COLLAR WITH PDC DRILLABLE PROFILE CW BALL, 7", 29 PPF, SPECIAL DRIFT DIAMETER 6-1/8" L-80/TYP-1 AS PER API 5CT, GAS TIGHT PREMIUM CONNECTION, NON ROTATING FEATURES FOR PLUGS MIN. INTERNAL YIELD PRESSURE: 8160 PSI MIN. COLLAPSE PRESSURE: 7030 PSI, MIN. TENSILE STRENGTH: 676 KLB (SHALL BE FULL INTERCHANGEABLE WITH NEW VAM)	NO	05								
07		TIE BACK SEAL ASSY (SEAL NIPPLE) 7", 29 PPF, SPECIAL DRIFT DIAMETER 6-1/8", PREMIUM CONNECTION L-80/TYP-1 AS PER API 5CT, BOX UP TEMPERATURE RATING: 250° - 300° F MIN. INTERNAL YIELD PRESSURE: 8160 PSI MIN. COLLAPSE PRESSURE: 7030 PSI, MIN. TENSILE STRENGTH: 676 KLB NUMBERS OF SEALS: SPECIFIED BY MANUFACTURE (MINIMUM 4 SET PACKING) SEALS OD: SPECIFIED BY MANUFACTURE LENGTH: 6 FT (AS PER ITEM 4) SEALS MATERIAL: HMBR (SHALL BE FULL INTERCHANGEABLE WITH NEW VAM)	NO	03								
08		LATCH DOWN COLLAR WITH PDC DRILLABLE PROFILE CW BALL, 7", 29 PPF, SPECIAL DRIFT DIAMETER 6-1/8" L-80/TYP-1 AS PER API 5CT, GAS TIGHT PREMIUM CONNECTION, NON ROTATING FEATURES FOR PLUGS MIN. INTERNAL YIELD PRESSURE: 8160 PSI MIN. COLLAPSE PRESSURE: 7030 PSI MIN. TENSILE STRENGTH: 676 KLB (SHALL BE FULL INTERCHANGEABLE WITH NEW VAM)	NO	03								



تاریخ تایید: ۱۳۵۵/۱۳/۴
مهر: [Signature]

[Signatures]



پروژه / DIRECT CHARGE MATERIALS REQUEST CONTINUATION SHEET

شماره تقاضا

REQUEST NO.

ردیف ITEM NO.	شرح کالا DESCRIPTION	مقدار REQUIRED QTY.	مبلغ VALUE (EST.)	تاریخ درخواست REQUEST DATE	تاریخ تایید APPROVAL DATE	تاریخ دریافت RECEIPT DATE	تاریخ تحویل DELIVERY DATE	تاریخ انقضای قرارداد CONTRACT EXPIRATION DATE	تاریخ اتمام کار WORK COMPLETION DATE	تاریخ بستن حساب ACCOUNT CLOSING DATE	تاریخ تسویه حساب ACCOUNT SETTLEMENT DATE	تاریخ پرداخت PAYMENT DATE	تاریخ تایید نهایی FINAL APPROVAL DATE
09	SETTING COLLAR (LG) 7" 29 PPF, SPECIAL DRIFT DIAMETER 6-1/8", PREMIUM CONNECTION, PIN x PIN L-80/TYPE-1 AS PER API 5CT, FOR CONNECTION TO RUNNING AND SETTING TOOLS MIN. INTERNAL YIELD PRESSURE: 8160 PSI MIN. COLLAPSE PRESSURE: 7030 PSI MIN. TENSILE STRENGTH: 676 KLB (SHALL BE FULL INTERCHANGEABLE WITH NEW VAM)	03											
10	TIE BACK SLEEVE PBR, 7", 29 PPF, SPECIAL DRIFT DIAMETER 6-1/8" THREAD: GAS TIGHT PREMIUM CONNECTION BOX DOWN (SHALL BE FULL INTERCHANGEABLE WITH NEW VAM) MATERIAL: L-80/TYPE-1 AS PER API 5CT MIN. INTERNAL YIELD PRESSURE: 8160 PSI MIN. COLLAPSE PRESSURE: 7030 PSI, MIN. TENSILE STRENGTH: 676 KLB LENGTH: 6 FT	03											
11	PACK OFF BUSHING 7", 29 PPF, SPECIAL DRIFT DIAMETER 6-1/8", PREMIUM CONNECTION, PIN x BOX L-80/TYPE-1 AS PER API 5CT, PDC DRILLABLE MIN. INTERNAL YIELD PRESSURE: 8160 PSI MIN. COLLAPSE PRESSURE: 7030 PSI MIN. TENSILE STRENGTH: 676 KLB (SHALL BE FULL INTERCHANGEABLE WITH NEW VAM)	03											
12	LINER WIPER PLUG 7" TO WIPE CEMENT INSIDE 29 PPF & 35 PPF LINER, PDC DRILLABLE, NON ROTATING TO LAND AND LOCK INSIDE LDC MATERIAL: SPECIFIED BY MANUFACTURE ELASTOMER MATERIAL: NBR TEMPERATURE RATING: 250° - 300° F	08											
13	PUMP DOWN PLUG MATERIAL: SPECIFIED BY MANUFACTURE, NON ROTATING TO LAND AND LOCK INSIDE WIPER PLUG ELASTOMER MATERIAL: NBR TEMPERATURE RATING: 250° - 300° F FOR 5" DRILL PIPE, PDC DRILLABLE	08											
14	FLOAT COLLAR 7", 29 PPF, SPECIAL DRIFT DIAMETER 6-1/8", L-80/TYPE-1 AS PER API 5CT, GAS TIGHT PREMIUM CONNECTION BOX UP, PIN DOWN, PDC DRILLABLE MIN. INTERNAL YIELD PRESSURE: 8160 PSI MIN. COLLAPSE PRESSURE: 7030 PSI, MIN. TENSILE STRENGTH: 676 KLB (SHALL BE FULL INTERCHANGEABLE WITH NEW VAM)	05											
15	SETTING TOOL FOR HYDRAULIC LINER HANGER 7" WITH ALL ACCESSORIES	02 -											



شماره تقاضا: ۱۳۵۸۳۱۴
شماره ثبت مناطق مرکزی ایران

Handwritten signatures and initials at the top right of the page.

شركة نفط منطقة مكة - ا. ا.