



ITEM NO.	WELD NO	توصيف العمل	ملاحظات	DESCRIPTION	شح 20"	مقدار	VALUE (EST.)	الكمية المطلوبة	CROSS REF.	ملاحظات	REQUEST NO.
						REQUIRED QTY.					
05	9			DIFFERENTIAL FILLUP SHOE W/BALL, 9-5/8", 47#, L-80, GAS TIGHT PREMIUM INTERCHANGABLE WITH N.VAM, PSL-2, SMLS, DD 8.525", AS PER API 5CT & API RP 10F & NACE MR0175, SOUR SERVICE, PDC DRILLABLE, MIN. COLLAPSE PRESSURE 4750 PSI, MIN. BURST PRESSURE 6870 PSI, MIN. PIPE BODY/JOINT YIELD STRENGTH 1086 Klb	20", 13-3/8" & 9-5/8" SHOE & COLLAR-TOP & BTM CMT PLUG	25					
06				DIFFERENTIAL FILLUP COLLAR, 9-5/8", 47#, L-80, GAS TIGHT PREMIUM INTERCHANGABLE WITH N.VAM, PSL-2, SMLS, DD 8.525", AS PER API 5CT & API RP 10F & NACE MR0175, SOUR SERVICE, PDC DRILLABLE, MIN. COLLAPSE PRESSURE 4750 PSI, MIN. BURST PRESSURE 6870 PSI, MIN. PIPE BODY/JOINT YIELD STRENGTH 1086 Klb		25					
07				DIFFERENTIAL FILLUP SHOE W/BALL, 9-5/8", 53.5#, T-95, GAS TIGHT PREMIUM INTERCHANGABLE WITH N.VAM, PSL-2, SMLS, DD 8.5" (SPECIAL DRIFT), AS PER API 5CT & API RP 10F & NACE MR0175, SOUR SERVICE, PDC DRILLABLE, MIN. COLLAPSE PRESSURE 7340 PSI, MIN. BURST PRESSURE 9410 PSI, MIN. PIPE BODY/JOINT YIELD STRENGTH 1477 Klb		10					
08				DIFFERENTIAL FILLUP COLLAR, 9-5/8", 53.5#, T-95, GAS TIGHT PREMIUM INTERCHANGABLE WITH N.VAM, PSL-2, SMLS, DD 8.5" (SPECIAL DRIFT), AS PER API 5CT & API RP 10F & NACE MR0175, SOUR SERVICE, PDC DRILLABLE, MIN. COLLAPSE PRESSURE 7340 PSI, MIN. BURST PRESSURE 9410 PSI, MIN. PIPE BODY/JOINT YIELD STRENGTH 1477 Klb		10					
09				TOP CMT PLUG FOR CSG 13-3/8", PDC DRILLABLE, DD 12.25"		50					
10				BTM CMT PLUG FOR CSG 13-3/8", PDC DRILLABLE, DD 12.25"		50					
11				TOP CMT PLUG FOR CSG 9-5/8", PDC DRILLABLE, DD 8.5"		50					
12				BTM CMT PLUG FOR CSG 9-5/8", PDC DRILLABLE, DD 8.5"		50					

١٤٥٨ - ١٧٧٧

شرکت نفت مناطق مرکزی

مکتبہ اسلامیہ دارالعلوم دیوبند



TERMS & CONDITIONS

مستندات فنی مربوط به VALVE شامل BACK AND BUMP PRESSURE , SEALING CAPACITY, OPENING AND CLOSING PRESSURE و همچنین مشخصات ایمپای، متریال، نرخ دبی عبوری، هکازیم و نحوه عملکرد می باشد ارائه گردد. در این خصوص مشخصات سیال و بندش آن می بایست ارائه گردد.

شرکت نفت مناطق مرکزی

